



605-GL 5 Gallon Bucket Pump

Ironside Lubricants 605-GL 5 Gallon Bucket Pump is a 60:1 ratio pump capable of Max 7,200 PSI output pressure. The output volume of the 605-GL 5 Gallon Bucket Pump provides sufficient amounts for most demanding applications requiring grease transfers up to 200 ft. The 605-GL 5 Gallon Bucket Pump is a durable pump that can be used in either a fixed or mobile application.

605-GL 5 Gallon Bucket Pump system comes complete with a 5 gallon drum cover (23121DC), 5 gallon follower plate (13012FP), and a 1/4" 10ft 10,000 psi discharge hose (14-10DH).

Optional 18" 10,000 psi 1/4" discharge hose with giant button head coupler, gauge tee, gauge, and swivel. (Part #141810KDH)



605-GL 5 Gallon Bucket Pump System

Pump Ratio	60:1
Delivery Rate (oz/min)	48
Working Pressure PSI	80-120
Air Inlet (NPTF)	1/4"
Grease Output (NPTF)	1/4"
Air Consumption (cfm)	12
Drum Size	5 gal. pail
Dia. Suction Tube (in)	1.26
Length of Suction Tube (in)	19.75
Length of Discharge Hose (ft)	10
ID of Discharge Hose	1/4"
Rated Pressure of Discharge Hose (PSI)	10,000
Shipping Weight (lb)	27